



| Chain |               | Pitch | Inner width | Inner link width | Outer plate width | Bushing $\varnothing$ | Pin $\varnothing$ | Width over pin | Projection over connecting link | Plate thickness | Plate height | Bearing area | Breaking load DIN | Weight      | Connecting links |
|-------|---------------|-------|-------------|------------------|-------------------|-----------------------|-------------------|----------------|---------------------------------|-----------------|--------------|--------------|-------------------|-------------|------------------|
| No.   |               | $p$   | $b_1$ min.  | $b_2$ max.       | $b_3$ min.        | $d_1$ max.            | $d_2$ max.        | $l_1$ max.     | $k$                             | $s$             | $g$ max.     | $f$          | $F_B$ min.        | $q \approx$ | No.              |
| 200   | <sup>26</sup> | 15,0  | 14,0        | 18,50            | 19,00             | 9,0                   | 6,0               | 26,0           | 2,0                             | 2,00            | 14,0         | 1,1          | 12,5              | 1,25        | 4,7,111,12       |
| 203   | <sup>26</sup> | 20,0  | 16,0        | 22,50            | 23,00             | 12,0                  | 8,0               | 33,0           | 3,0                             | 3,00            | 19,0         | 1,8          | 25,0              | 2,10        | 4,7,11,111,12    |
| 206   | <sup>26</sup> | 25,0  | 18,0        | 24,50            | 25,00             | 15,0                  | 10,0              | 37,0           | 3,5                             | 3,00            | 24,0         | 2,5          | 31,5              | 2,60        | 4,7,111,12       |
| 209   | <sup>26</sup> | 30,0  | 20,0        | 28,50            | 29,00             | 17,0                  | 11,0              | 43,0           | 3,5                             | 4,00            | 28,0         | 3,1          | 40,0              | 4,00        | 4,7,111,12       |
| 212   | <sup>26</sup> | 35,0  | 22,0        | 30,50            | 31,00             | 18,0                  | 12,0              | 46,0           | 4,5                             | 4,00            | 30,0         | 3,7          | 50,0              | 4,30        | 4,7,111,12       |
| 215   | <sup>26</sup> | 40,0  | 25,0        | 35,50            | 36,00             | 20,0                  | 14,0              | 53,0           | 4,5                             | 5,00            | 35,0         | 5,0          | 63,0              | 6,00        | 4,7,111,12       |
| 218   | <sup>26</sup> | 45,0  | 30,0        | 42,50            | 43,00             | 22,0                  | 16,0              | 63,0           | 4,5                             | 6,00            | 40,0         | 6,8          | 80,0              | 8,00        | 4,7,111,12       |

<sup>26</sup> Connecting link No. 111 (S) with double cottered pin, i.e. projection k on both chain sides

For details on orders and enquiries see page 131. Sprockets on request.

Chain speeds with bush chains up to a pitch:

- of 20 mm ... up to 5 m/s
- of 40 mm ... up to 4 m/s
- more than 40 mm ... up to 3 m/s

**Connecting links:** According to ISO (...)



No. 4 (B)  
Inner link



No. 7 (A)  
Outer link  
(to be riveted)



No. 11 (E)  
Spring clip  
connecting link



No. 111 (S)  
Connecting link  
with cottered pin



No. 12 (L)  
Single  
cranked link