


SPANN-BOX® SIZE 30

Spann-Box® size 30 provides high quality at the same time as being economically priced. The robust plastic housing gives high resistance to corrosion.

DIN 8187 chain no.	Pitch in mm	Pitch in inch	Simplex	Duplex	Triplex
≤ 06B	-	-			
06B	9.525	3/8			
08B	12.7	1/2			
10B	15.875	5/8			
12B	19.05	3/4			

Tension force		Light	Heavy
	1 released spring	58 – 32N	132 – 60N
	2 released springs	116 – 64N	264 – 120N
	3 released springs	174 – 96N	396 – 180N
	Tension distance	40mm	40mm

SPANN-BOX® SIZE 30

with arc segment profile

Stainless steel screws and springs



Applications

- Environments with a risk of corrosion
- No high mechanical stresses

Tensioning pressure

- Choice of light or heavy spring force

Attachment

- Installed underneath the chain
- Bore holes in the housing

DIN 8187 chain no.	B mm	Light tension force article no.	Heavy tension force article no.	Availability
≤06B-1 (U profile)	20	281 030 001	281 030 002	●
08B-1	20	281 030 003	281 030 004	●
10B-1	20	281 030 005	281 030 006	●
12B-1	20	281 030 007	281 030 008	●
16B-1	20	281 030 009	281 030 010	●
05B-2	20	281 030 011	281 030 012	●
06B-2	20	281 030 013	281 030 014	●
08B-2	20	281 030 015	281 030 016	●
10B-2	25	281 030 017	281 030 018	●
12B-2	30	281 030 019	281 030 020	●
05B-3	20	281 030 021	281 030 022	○
06B-3	25	281 030 023	281 030 024	●
08B-3	30	281 030 025	281 030 026	●
10B-3	40	281 030 027	281 030 028	○
12B-3	45	281 030 029	281 030 030	○

Special designs on request

● Stocked ○ Available within 10 days

